



「Urofino」 Disposable Electronic Flexible Ureteroscope

Shanghai SeeGen Photoelectric Technology Co., Ltd.

SEEGEN
vision borderless
V 2.2

Less weightness and ergonomic design make the scope procedure more easier to control.

Easy to control all scope procedure.

2 light guide lens make the viewing more bright.

Taper-shape distal tip makes insertion more easier.

Bending angle 275°

Model	UV-US100-H
Field of view	110°
Depth of view	5-50mm
Deflection up/down	275°/275°
Insertion dia.	3.0mm
Distal end dia.	3.0mm
Working length	750mm
Working channel	1.2mm

High resolution Image.

Image Process Specification	
Power	Voltage 100-240 VAC
	Frequency 50/60 Hz
	Rated input 45 VA
illumination	Lamp 2W LED
	Color temperature 3,000K-7,000K
Function	White balance, Luminance control(+/-), Enhance(0,1,2), Zoom(x1,x2,x3), Freeze, Snap, Record, USB storage)
Output	DVI*1, S-Video*1, CVBS*1
Storage	USB (FAT 32)
Dimensions	350mm(W) * 130mm(H) * 425mm(D)
Weight	8 kg

Shanghai SeeGen Photoelectric Technology Co., Ltd.
Add.: 3 Floor, Building No.14299 Jindu Road, Minhang Dist., Shanghai China
Email: info@seegen.com.cn